



PRIME AV SOLUTIONS

ROE Ruby 2.6 Curve



Title	RB-C2.6
Pixel Pitch	2.604mm
LED Configuration	SMD 1515 Black
Max Brightness Calibrated	1500nits
Panel Dimensions	500mm x 500mm x 108mm 19.7" x 19.7" x 4.25"
Panel Resolutions (H x V)	192 x 192
Weight Per Panel	8.3kg 18.31lbs
Power Consumption Max/Average	160W / 80W
BTU Max/Average	545 / 250
Transparency	Solid
Servicability	Rear
Curving (Concave & Convex)	Concave 30° ~ Convex 30°
Viewing Angle Vertical	140°
Viewing Angle Horizontal	140°
Refresh Rate	7680Hz
With Depth	16bit

Operational Temp/Humidity	-20°C ~ 45°C, 10% ~ 90% RH -4°F ~ 113°F, 10% ~ 90% RH
Storage Temp/Humidity	-40°C ~ 60°C, 10% ~ 90% RH -40°F ~ 140°F, 10% ~ 90% RH
IP Rating	Indoor
Certifications	CE, ETL, FCC, UKCA
Scan Ratio	1/12
Max. Hanging	20 panels
Max. Stacking	12 panels
Processing	Megapixel

Please note: The specifications are for reference only, actual values may vary.